



Note: Pictures are for illustration only, and may not reflect the listed model.



| GENERAL | | | | | |
|---------------|--------------|------------------|----------------|------------|----------|
| REFRIGERANT | VOLTAGE | EVAPORATOR MODEL | DEFROST SCHEME | CONTROLLER | LISTINGS |
| R-448A/R-449A | 208-230/60/1 | WL6E035DEAS | ELECTRIC | THERMOSTAT | UL/CUL |

| BTUH CAPACITY (At Saturated Suction Temperature (SST) with 10° TD) | | | | | | | |
|--|-------|-------|----|----|----|----|----|
| -30 | -20 | -10 | 20 | 25 | 30 | 35 | 45 |
| 3,850 | 4,000 | 4,150 | - | - | - | - | - |

| DIMENSIONAL DATA | | | | INSTALLATION | | |
|------------------|------|-------|----------|--------------|---------|------------------|
| OVERALL (inches) | | | WT (lbs) | CONNECTIONS | | REFRIGERANT TYPE |
| L | W | H | | LIQUID | SUCTION | |
| 27.125 | 15.5 | 16.75 | 41 | 3/8 | 7/8 | R-448A/R-449A |

| ELECTRICAL | | DEFROST AMPS | | EXPANSION VALVE | |
|--------------|----------|--------------|---------|-----------------|--------------|
| FAN QUANTITY | FAN AMPS | 1 PHASE | 3 PHASE | PART NUMBER | MODEL NUMBER |
| | | 1 | 0.5 | 4.9 | N/A |

