



Note: Pictures are for illustration only, and may not reflect the listed model.



| GENERAL       |              |                 |                  |    |      |          |
|---------------|--------------|-----------------|------------------|----|------|----------|
| REFRIGERANT   | VOLTAGE      | COMPRESSOR TYPE | COMPRESSOR MODEL | HP | AWEF | LISTINGS |
| R-448A/R-449A | 208-230/60/1 | Scroll          | ZF03KAE-PFV      | 1  | -    | UL/CUL   |

| BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser) |       |       |    |    |    |    |    |
|---|-------|-------|----|----|----|----|----|
| -30   | -20   | -10   | 20 | 25 | 30 | 35 | 45 |
| 2,213   | 2,949 | 3,808 | -  | -  | -  | -  | -  |

| DIMENSIONAL DATA          |    |    |          |           |           |
|---------------------------|----|----|----------|-----------|-----------|
| OVERALL (to nearest inch) |    |    | WT (lbs) | BASE SIZE | BASE/HOOD |
| L                         | W  | H  |          |           |           |
| 22                        | 27 | 18 | 180      | M1        | 011M      |

| INSTALLATION  |                                 |             |         |  |
|---------------|---------------------------------|-------------|---------|--|
| REFRIGERANT   | RECEIVER TANK (lbs)<br>90%/90°F | CONNECTIONS |         | ESTIMATED TOTAL<br>HEAT REJECTION (BTUH) |
|               |                                 | LIQUID      | SUCTION |  |
| R-448A/R-449A | 8.1                             | 3/8         | 7/8     | 5,522                                    |

| ELECTRICAL  |                     |                    |            |              |                      |                             |  |
|-------------|---------------------|--------------------|------------|--------------|----------------------|-----------------------------|--|
| MCA         | MOP                 | COMP VOLTS         | COMP PHASE | COMP HZ      | COMP RLA             | COMP LRA                    |  |
| 13          | 15                  | 208-230            | 1          | 60           | 6.1                  | 42.3                        |  |
| FAN PHASE   | FAN HZ              | FAN FLA            | FAN HP     | FAN QUANTITY | MAX EVAP FAN<br>AMPS | MAX EVAP DEF<br>HEATER AMPS |  |
| 1           | 60                  | 0.5                | 1/20       | 1            | 3                    | 10.0                        |  |
| OTHER VOLTS | OTHER LOAD<br>PHASE | OTHER LOAD<br>AMPS |            |              |                      |                             |  |
| 208-230     | 1                   | 0.5                |            |              |                      |                             |  |

