



Note: Pictures are for illustration only, and may not reflect the listed model.



| GENERAL | | | | | | |
|---------------|--------------|-----------------|------------------|------|------|----------|
| REFRIGERANT | VOLTAGE | COMPRESSOR TYPE | COMPRESSOR MODEL | HP | AWEF | LISTINGS |
| R-448A/R-449A | 208-230/60/1 | Hermetic | ASE20C4E-IAV | 0.25 | 7.6 | UL/CUL |

| BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser) | | | | | | | |
|---|-----|-----|-------|-------|-------|----|----|
| -30 | -20 | -10 | 20 | 25 | 30 | 35 | 45 |
| - | - | - | 2,728 | 3,050 | 3,399 | - | - |

| DIMENSIONAL DATA | | | | | | |
|---------------------------|----|----|----------|-----------|-----------|--|
| OVERALL (to nearest inch) | | | WT (lbs) | BASE SIZE | BASE/HOOD | |
| L | W | H | | | | |
| 22 | 27 | 18 | 180 | M1 | 011M | |

| INSTALLATION | | | | | | |
|---------------|---------------------------------|-------------|---------|--|--|--|
| REFRIGERANT | RECEIVER TANK (lbs) 90%/90°F | CONNECTIONS | | | ESTIMATED TOTAL HEAT REJECTION (BTUH) | |
| | | LIQUID | SUCTION | | | |
| R-448A/R-449A | 8.1 | 3/8 | 5/8 | | 4,132 | |

| ELECTRICAL | | | | | | | |
|-------------|---------------------|--------------------|------------|--------------|----------------------|-----------------------------|--|
| MCA | MOP | COMP VOLTS | COMP PHASE | COMP HZ | COMP RLA | COMP LRA | |
| 19 | 20 | 208-230 | 1 | 60 | 2.7 | 17.5 | |
| FAN PHASE | FAN HZ | FAN FLA | FAN HP | FAN QUANTITY | MAX EVAP FAN AMPS | MAX EVAP DEF HEATER AMPS | |
| 1 | 60 | 0.5 | 1/20 | 1 | 4 | 15.0 | |
| OTHER VOLTS | OTHER LOAD PHASE | OTHER LOAD AMPS | | | | | |
| 208-230 | 1 | 0.5 | | | | | |

