



Note: Pictures are for illustration only, and may not reflect the listed model.



GENERAL						
REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	208-230/60/1	Hermetic	ASE32C5E-CAV	0.33	7.6	UL/CUL

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
-	-	-	4,195	4,639	5,095	-	-

DIMENSIONAL DATA						
OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD	
L	W	H				
22	27	18	180	M1	011M	

INSTALLATION						
REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS			ESTIMATED TOTAL HEAT REJECTION (BTUH)	
		LIQUID	SUCTION			
R-448A/R-449A	7.1	3/8	5/8		6,453	

ELECTRICAL							
MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	
19	20	208-230	1	60	4.5	26	
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	
1	60	0.5	1/20	1	4	15.0	
OTHER VOLTS	OTHER LOAD PHASE	OTHER LOAD AMPS					
208-230	1	0.5					

