



Note: Pictures are for illustration only, and may not reflect the listed model.



| GENERAL | | | | | | |
|---------------|----------|-----------------|------------------|------|------|----------|
| REFRIGERANT | VOLTAGE | COMPRESSOR TYPE | COMPRESSOR MODEL | HP | AWEF | LISTINGS |
| R-448A/R-449A | 460/60/3 | Scroll | ZS09KAE-TFD | 1.25 | 7.6 | UL/CUL |

| BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser) | | | | | | | |
|---|-----|-----|--------|--------|--------|--------|--------|
| -30 | -20 | -10 | 20 | 25 | 30 | 35 | 45 |
| - | - | - | 10,006 | 11,115 | 12,325 | 13,645 | 16,647 |

| DIMENSIONAL DATA | | | | | |
|---------------------------|----|----|----------|-----------|-----------|
| OVERALL (to nearest inch) | | | WT (lbs) | BASE SIZE | BASE/HOOD |
| L | W | H | | | |
| 38 | 27 | 18 | 240 | M2 | 021M |

| INSTALLATION | | | | |
|---------------|---------------------------------|-------------|---------|--|
| REFRIGERANT | RECEIVER TANK (lbs) 90%/90°F | CONNECTIONS | | ESTIMATED TOTAL HEAT REJECTION (BTUH) |
| | | LIQUID | SUCTION | |
| R-448A/R-449A | 12.0 | 1/2 | 7/8 | 14,422 |

| ELECTRICAL | | | | | | | |
|-------------|---------------------|--------------------|------------|--------------|----------------------|-----------------------------|--|
| MCA | MOP | COMP VOLTS | COMP PHASE | COMP HZ | COMP RLA | COMP LRA | |
| 19 | 20 | 460 | 3 | 60 | 3.4 | 28 | |
| FAN PHASE | FAN HZ | FAN FLA | FAN HP | FAN QUANTITY | MAX EVAP FAN AMPS | MAX EVAP DEF HEATER AMPS | |
| 1 | 60 | 0.5 | 1/20 | 2 | 2 | 15.0 | |
| OTHER VOLTS | OTHER LOAD PHASE | OTHER LOAD AMPS | | | | | |
| 460 | 1 | 0.5 | | | | | |

