



# MSLD010AB CONDENSING UNIT



Note: Pictures are for illustration only, and may not reflect the listed model.



### GENERAL

REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	208-230/60/1	Scroll	ZF03KAE-PFV	1	-	UL/CUL

### BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)

-30	-20	-10	20	25	30	35	45
2,213	2,949	3,808	-	-	-	-	-

### BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)

-30	-20	-10	20	25	30	35	45
1,903	2,624	3,389	-	-	-	-	-

### DIMENSIONAL DATA

OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD
L	W	H			
22	27	18	180	M1	011M

### INSTALLATION

REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS		ESTIMATED TOTAL HEAT REJECTION (BTUH)
		LIQUID	SUCTION	
R-448A/R-449A	7.1	3/8	7/8	-

### ELECTRICAL

MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD DATA	
13	15	208-230	1	60	6.1	42.3	VOLTS	208-230
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	PHASE	1
1	60	0.5	1/20	1	3	10.0	AMPS	0.5

