



MSLD012RC CONDENSING UNIT



Note: Pictures are for illustration only, and may not reflect the listed model.



| GENERAL | | | | | | |
|---------------|--------------|-----------------|------------------|------|------|----------|
| REFRIGERANT | VOLTAGE | COMPRESSOR TYPE | COMPRESSOR MODEL | HP | AWEF | LISTINGS |
| R-448A/R-449A | 208-230/60/3 | Scroll | ZF04KAE-TF5 | 1.25 | - | UL/CUL |

| BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser) | | | | | | | |
|---|-------|-------|----|----|----|----|----|
| -30 | -20 | -10 | 20 | 25 | 30 | 35 | 45 |
| 2,925 | 3,824 | 4,947 | - | - | - | - | - |

| BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser) | | | | | | | |
|--|-------|-------|----|----|----|----|----|
| -30 | -20 | -10 | 20 | 25 | 30 | 35 | 45 |
| 2,516 | 3,403 | 4,403 | - | - | - | - | - |

| DIMENSIONAL DATA | | | | | |
|---------------------------|----|----|----------|-----------|-----------|
| OVERALL (to nearest inch) | | | WT (lbs) | BASE SIZE | BASE/HOOD |
| L | W | H | | | |
| 22 | 27 | 18 | 180 | M1 | 011M |

| INSTALLATION | | | | |
|---------------|---------------------------------|-------------|---------|--|
| REFRIGERANT | RECEIVER TANK (lbs) 90%/90°F | CONNECTIONS | | ESTIMATED TOTAL HEAT REJECTION (BTUH) |
| | | LIQUID | SUCTION | |
| R-448A/R-449A | - | 1/2 | 7/8 | - |

| ELECTRICAL | | | | | | | |
|------------|--------|------------|------------|--------------|----------------------|-----------------------------|--------------------|
| MCA | MOP | COMP VOLTS | COMP PHASE | COMP HZ | COMP RLA | COMP LRA | OTHER LOAD DATA |
| 13 | 15 | 208-230 | 3 | 60 | 6.6 | 55.4 | |
| FAN PHASE | FAN HZ | FAN FLA | FAN HP | FAN QUANTITY | MAX EVAP FAN AMPS | MAX EVAP DEF HEATER AMPS | PHASE 1 |
| 1 | 60 | 0.5 | 1/20 | 1 | 4 | 2.7 | AMPS 0.5 |

