



MSLD035RE CONDENSING UNIT



Note: Pictures are for illustration only, and may not reflect the listed model.



GENERAL						
REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	460/60/3	Scroll	ZF11K4E-TFD	3.5	-	UL/CUL

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
9,306	11,958	15,110	-	-	-	-	-

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
8,003	10,642	13,448	-	-	-	-	-

DIMENSIONAL DATA						
OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD	
L	W	H				
30	31	26	250	M3	031M	

INSTALLATION				
REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS		ESTIMATED TOTAL HEAT REJECTION (BTUH)
		LIQUID	SUCTION	
R-448A/R-449A	-	1/2	7/8	-

ELECTRICAL							
MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD DATA
14	15	460	3	60	5.8	44	
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	PHASE 1
1	60	1.6	1/4	1	5	5.0	AMPS 0.5

