



# MSLD150RE CONDENSING UNIT



Note: Pictures are for illustration only, and may not reflect the listed model.



### GENERAL

REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	460/60/3	Scroll	ZF49K5E-TFD	15	-	UL/CUL

### BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)

-30	-20	-10	20	25	30	35	45
38,088	49,106	61,799	-	-	-	-	-

### BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)

-30	-20	-10	20	25	30	35	45
32,755	43,705	55,001	-	-	-	-	-

### DIMENSIONAL DATA

OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD
L	W	H			
64	44	40	540	M6	062M

### INSTALLATION

REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS		ESTIMATED TOTAL HEAT REJECTION (BTUH)
		LIQUID	SUCTION	
R-448A/R-449A	32.0	7/8	2 1/8	-

### ELECTRICAL

MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD DATA
32	45	460	3	60	18.1	139	
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	PHASE 1
1	60	2.9	1/3	2	3	5.0	AMPS 0.5

