

ITEM NO. _____
 PROJECT _____
 LOCATION _____
 DATE _____ QTY. _____

FUSION™ MBRGM/MBFGM-HB SERIES

Bottom Mounted Swing Glass Door Merchandisers With Lighted Sign

REFRIGERATORS FREEZERS

- | | |
|------------------------------------|------------------------------------|
| <input type="checkbox"/> MBRGM23HB | <input type="checkbox"/> MBFGM23HB |
| <input type="checkbox"/> MBRGM48HB | <input type="checkbox"/> MBFGM48HB |
| <input type="checkbox"/> MBRGM72HB | <input type="checkbox"/> MBFGM72HB |



MBRGM48HB/MBFGM48HB



FEATURES

CONSTRUCTION

- Black vinyl coated exterior with white interior and stainless steel floor
- Foamed-in-place with polyurethane insulation
- Top LED backlit panel
- Two LED light strips per door for maximum product illumination
- Four heavy duty shelves, adjustable in 1/2" increments, per door and capable of supporting 125 lbs.
- Product label strips on shelves
- Heavy duty factory-installed casters
- Electronic adjustable temperature control with digital display

DOORS

- Self-closing swing doors with energy efficient triple pane glass
- Standard lock for each door
- Magnetic gaskets

REFRIGERATION


- Self-contained bottom mounted, air cooled refrigeration system with coated evaporator coil
- Automatic defrost
- Condensate is collected and automatically evaporated from an energy efficient vaporizer
- Refrigerant flow is controlled by a capillary tube
- R290 refrigerant
- Temperature range:
 - Refrigerators: +34°F to +40°F (+1°C to +4°C)
 - Freezers: -10°F to +10°F (-23°C to -12°C)

WARRANTY


- Standard limited three year parts and labor
- Additional two year coverage on compressor part

TECHNICAL SPECIFICATIONS


Models	Refrigerators			Freezers		
	MBRGM23HB	MBRGM48HB	MBRGM72HB	MBFGM23HB	MBFGM48HB	MBFGM72HB
Crated Weight (lbs) (kg)	330 (150)	551 (250)	740 (336)	342 (155)	564 (256)	820 (372)
Crated Height (in) (mm)	84.6 (2149)	84.6 (2149)	84.6 (2149)	84.6 (2149)	84.6 (2149)	84.6 (2149)
Crated Width (in) (mm)	28.3 (719)	55.5 (1410)	82.6 (2098)	28.3 (719)	55.5 (1410)	82.6 (2098)
Crated Depth (in) (mm)	34.8 (884)	34.8 (884)	34.8 (884)	34.8 (884)	34.8 (884)	34.8 (884)
Interior Height (in) (mm)	52.0 (1321)	52.0 (1321)	52.0 (1321)	52.0 (1321)	52.0 (1321)	52.0 (1321)
Interior Width (in) (mm)	22.2 (564)	49.4 (1255)	76.4 (1941)	22.2 (564)	49.4 (1255)	76.4 (1941)
Interior Depth (in) (mm)	27.6 (701)	27.6 (701)	27.6 (701)	27.6 (701)	27.6 (701)	27.6 (701)
Overall Height (in) (mm)	80.75 (2051)	80.75 (2051)	80.75 (2051)	80.75 (2051)	80.75 (2051)	80.75 (2051)
Overall Width (in) (mm)	27 (686)	54 (1372)	81 (2057)	27 (686)	54 (1372)	81 (2057)
Overall Depth (in) (mm)	32 (813)	32 (813)	32 (813)	32 (813)	32 (813)	32 (813)
Gross Cubage (CuFt) (L)	23.0 (651)	49.0 (1388)	72.0 (2039)	23.0 (651)	49.0 (1388)	72.0 (2039)
Number of Shelves	4	8	12	4	8	12
Shelf Area (SqFt) (Sqm)	18.9 (1.8)	43.4 (4.0)	67.9 (6.3)	18.9 (1.8)	43.4 (4.0)	67.9 (6.3)
Number of Casters	4	4	6	4	4	6
Condensing Unit Size	3/8 HP	1/2 HP	3/4 HP	1/2 HP	3/4 HP	3/4 HP
Refrigerant	R290	R290	R290	R290	R290	R290
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115-230/60/1
NEMA Plug Configuration	5-15P	5-15P	5-15P	5-15P	5-15P	L14-20P
Total Amp Draw	3.0	4.5	7.5	8.0	9.0	9.0




MBRGM23HB/MBFGM23HB PLAN VIEW



MBRGM23HB/MBFGM23HB ELEVATION VIEW




**ALL MODELS
SIDE VIEW**




MBRGM48HB/MBFGM48HB PLAN VIEW




MBRGM48HB/MBFGM48HB ELEVATION VIEW



GRAPHIC PANEL DIMENSIONS




MBRGM72HB/MBFGM72HB PLAN VIEW




MBRGM72HB/MBFGM72HB ELEVATION VIEW

LISTINGS**HOOKUP**

Via plug in, 9.8 foot long flexible three wire 14/3 cord with molded plug.



NEMA 5-15P
(all models except
MBFGM72HB)



NEMA L14-20P
(MBFGM72HB)

BID SPECIFICATIONS

Item no. MBRGM/MBFGM _____ HB
Provide _____ ()
Bottom Mounted Swing Glass Door
Merchandise(s) with lighted sign
Master-Bilt® model MBRGM/
MBFGM _____ HB.

Merchandise to be constructed of
black vinyl coated exterior with white
interior and stainless steel floor. Other
standard features will include a top LED
backlit panel, two LED light strips per

door and factory-installed casters.

Merchandise will also feature four
heavy-duty shelves, adjustable in 1/2"
increments, per door and capable of
supporting 125 lbs. each.

Locking swing doors will be self-
closing with triple pane glass and
magnetic gaskets.

Refrigeration system will use R290
refrigerant in all models. The operating
temperature range will be 34° to 40°F

(1° to 4° C) for refrigerators and -10°
to +10°F (-23° to -12°C) for freezers.

Merchandise to have standard
limited three year parts and labor
with additional two year coverage on
compressor part.

Merchandise to be ETL listed in the
U.S. and Canada and ETL Sanitation
listed.

**NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity.
All specifications within this publication subject to change without notice.**