



# MSLD012HCQ CONDENSING UNIT



Note: Pictures are for illustration only,  
and may not reflect the listed model.



GENERAL						
REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	208-230/60/3	Scroll	ZF04KAE-TF5	1.25	-	UL/CUL

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
2,925	3,824	4,947	-	-	-	-	-

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
2,516	3,403	4,403	-	-	-	-	-

DIMENSIONAL DATA						
OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD	
L	W	H				
22	27	18	180	M1	011M	

INSTALLATION					
REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS		With Quick-Connects and Precharged Refrigerant	ESTIMATED TOTAL HEAT REJECTION (BTUH)
		LIQUID	SUCTION		
R-448A/R-449A	7.1	3/8	7/8		7,197

ELECTRICAL							
MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD DATA
13	15	208-230	3	60	6.6	55.4	
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	PHASE 1
1	60	0.5	1/20	1	4	8.0	AMPS 0.5

