



MSLD015ABQD CONDENSING UNIT



Note: Pictures are for illustration only,
and may not reflect the listed model.



GENERAL

REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-448A/R-449A	208-230/60/1	Scroll	ZF05KAE-PFV	1.5	-	UL/CUL

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)

-30	-20	-10	20	25	30	35	45
3,319	4,401	5,646	-	-	-	-	-

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)

-30	-20	-10	20	25	30	35	45
2,854	3,917	5,025	-	-	-	-	-

DIMENSIONAL DATA

OVERALL (to nearest inch)			WT (lbs)	BASE SIZE	BASE/HOOD
L	W	H			
22	27	18	180	M1	011M

INSTALLATION

REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS		With Quick-Connects and Precharged Refrigerant	ESTIMATED TOTAL HEAT REJECTION (BTUH)
		LIQUID	SUCTION		
R-448A/R-449A	7.1	3/8	7/8		8,033

ELECTRICAL

MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD DATA	
19	20	208-230	1	60	8.7	55	VOLTS	208-230
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	PHASE	1
1	60	0.5	1/20	1	5	15.0	AMPS	0.5

