

MSMD060AE CONDENSING UNIT





Note: Pictures are for illustration only, and may not reflect the listed model.



GENERAL							
REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS	
R-448A/R-449A	460/60/3	Scroll	ZS45K4E-TFD	6	5.61	UL/CUL	

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90 ⁰ Ambient at Condenser)								
-30	-20	-10	20	25	30	35	45	
-	-	-	49,180	53,983	58,932	64,017	74,562	
BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)								
-30	-20	-10	20	25	30	35	45	
-	-	-	45,245	49,664	54,218	58,896	68,597	

DIMENSIONAL DATA						
	OVERALL (to nearest inch)				
L	W	Н	WT (lbs)	BASE SIZE	BASE/HOOD	
48	31	26	300	M5	051M	

INSTALLATION							
	RECEIVER TANK (lbs)	CONNE	CTIONS		ESTIMATED TOTAL		
REFRIGERANT	90%/90°F	LIQUID	SUCTION		HEAT REJECTION (BTUH)		
R-448A/R-449A	15.2	1/2	7/8		74,025		

ELECTRICAL								
MCA	МОР	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD	
25	30	460	3	60	9.3	75	DATA	
					MAX EVAP FAN	MAX EVAP DEF	VOLTS	460
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	AMPS	HEATER AMPS	PHASE	1
1	60	1.6	1/4	2	6	20.0	AMPS	0.5

