



WALK-IN SHELVING SYSTEMS




Most options are available two weeks from receipt of order.
Please contact us for specific questions.

FEATURES

- Shelving kits specifically designed for each walk-in configuration
- Offered as an optional extra
- Kits are shipped with the walk-in so all necessary components are at your location promptly
- Shelving sets coded to correspond to the walk-in configuration ordered
- Offered in either three or four tier
- Norlake shelving system types:
 - A. **Green Kote™** - Green epoxy-coated shelves with 15-year guarantee against corrosion
 - B. **Chrome Kote™** - Nickel chrome-plated shelves
- Shelving posts engineered for maximum strength
- Shelves are adjustable on 1" centers
- All shelves are NSF listed
- Special clips utilized to gain the maximum square footage of storage space for each model
- Standard lengths: 24", 30", 36", 42", 48", 54", 60" and 72"
- Standard depths: 14", 18" and 24"
- Standard heights: 64" (3-tier), 74" (4-tier) and 86" (5-tier)
- Wire shelving is ideal for storage of all refrigerated or frozen products as well as non-refrigerated storage



TYPICAL SHELVING SYSTEM LAYOUTS FOR NORLAKE WALK-INS



SPECIFICATIONS

SHELVES:

Shelves to have #9 (.148") gauge crosswires spaced 3/4" on centers with crossbraces 1/4" (.192") minimum of 4-3/4" on center.

SHELF FRAMES:

Channel to be 9/16" x 1" x .075" thick.

SHELF COLLARS

A round tapered 1-5/16" high steel collar to be welded at each corner.

FINISHES:

A. Green Kote™

- Electrostatically-applied green baked epoxy over zinc steel and brite basic wire.
- Thickness: 4-7 mill.

B. Chrome Kote™

- Plated quality wire and steel
- Surface nickel chrome plated

POSTS:

Posts to be .062" thick 1" O.D. round tubing notched every 1" on each corner of the post.

POST LEVELER:

Installed on the bottom of each post is nylon housing for a steel leveler 3/8"-16 x 1-3/4".

